# Safety Data Sheet

BOSS" 801 Neutral Cure Silicone Adhesive

#### Section 1. Identification

Product Identifier

er BOSS" 801 Neutral Cure Silicone Adhesive

Synonyms

02505CL10; 02505WH10; 02505GY10; 03217CL01; 03217WH10;

C04052CL; C04052WH; C04052GY

Manufacture Stock

Numbers

N/A

Recommended use Uses advised against Refer to Technical Data Refer to Technical Data

Manufacturer Contact

Address

SOUDAL Accumetric

350 Ring Road

Elizabethtown, KY, 42701

**USA** 

Phone

Emergency

Fax

Phone

(270) 769-3385

(800) 424- N/A

9300 Chemtrec

### Section 2. Hazards I dentification

HAZARDOUS TO THE AQUATIC ENVIROMENT - LONG-TERM

HAZARD - Category 3

SENSITIZATION - SKIN - Category 1

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) -

Category 2

Signal Word Pictogram

Warning





Hazard Statements

Causes serious eye irritation

Harmful to aquatic life with long lasting effects

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated

exposure.

Precautionary Statements Response Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

insing.

If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the

workplace.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Ingredients of unknown 0% toxicity

Hazards not Otherwise None known

Classified

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid Measures

Eye Contact Immediately flush with water for 15 minutes.

Skin Contact Remove from skin and immediately flush with water for 15

minutes. Get medical attention if irritation or ill effects develop or

persist.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate

medical attention.

Ingestion Get medical attention.

Comments Treat according to person's condition and specifics of exposure.

### Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Unsuitable

Extinguishing Media

Auto-ignition

Temperature

Lower Explosive Limit

(%)

Upper Explosive Limit

(%)

Extinguishing Media

Special Fire Fighting Procedures

N/A

N/A

Not determined

Not applicable

Not applicable

Carbon Dioxide, Dry Chemical, Foam, Water, Water Fog or

Spray

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire or Explosion Hazards

None known

### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

### Section 7. Handling and Storage

Handling Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep

container closed. Do not take internally. Use reasonable care.

Keep container closed and store in a cool, well ventilated area,

away from water or moisture.

### Section 8. Exposure Controls/Personal Protecction

Occupational Exposure Limits

Storage

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Vinyl Oximino Silane	N/A	N/A	N/A
Methyl Oximino Silane	N/A	N/A	N/A
N-beta-(aminoethyl)-gamma-	10	6	N/A
aminopropyltrimethoxysilane	mg/m3	mg/m3	
Dimethylpolysiloxane	N/A	N/A	N/A
Amorphous fumed silica	N/A	N/A	N/A
Distillates (petroleum), straight-run middle	N/A	N/A	N/A

Personal Protective Equipment

Component Exposure

Limits

**Engineering Controls** 

Eye Protection Skin Protection

**Respiratory Protection** 

N/A

Methyl ethyl ketoxime is formed upon contact with water or moisture in the air. Provide adequate ventilation to control exposures to within the exposure guideline of 2 ppm (TWA).

Local Ventilation: Recommended General Ventilation:

Recommended

Use proper protection - safety glasses as a minimum.

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and throughly cleaned before reuse. Chemical protective gloves are

recommended. Suitable Gloves: Silver Shield. 4H.

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls. Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control

methyl ethyl ketoxime within the exposure guidelines or use

respiratory protection.

Comment

# Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Slight
Odor Threshold	N/A
Solubility	Insoluble
Partition coefficient Water/n- octanol	N/A
Viscosity	850,000 cPs
Specific Gravity	1.03
Density lbs/Gal	8.55
Pounds per Cubic Foot	N/A
Flash Point	Not determined
FP Method	N/A
Ph	Not applicable
Melting Point	Not determined
Boiling Point	Not determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Not determined

NoteThe above information is not intended for use in preparing product specifications. Contact SOUDAL Accumentric before writing specifications.

# Section 10. Stability and Reactivity

Hazardous Will not occur Polymerization

Materials to Avoid / Oxidiz Incompatibility

Oxidizing material can cause a reaction.

Chemical Stability Stable
Conditions to Avoid None known

### Section 11. Toxicological Information

Special Hazard Information on Component

Methyl Oximino Silane (22984-54-9) Possible skin sensitizer Vinyl

Oximino Silane (2224-33-1) Possible skin sensitizer

Component Toxicology Information

Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be

maintained as low as achievable.

Carcinogenicity No ingredient in this product is an IARC, NTP or OSHA listed

carcinogen.

Mutagenicity This product is not known to be a mutagen.

Teratogenicidad No se tiene conocimiento de que este producto sea terat—geno.

Reproductive Toxin This product is not known to be a reproductive toxin.

### Section 12. Ecological Information

**Environmental Effects** 

Complete information is not yet available.

Fate and Effects in Complete information is not yet available.

Waste Water Treatment

**Plants** 

Environmental Fate and Complete information is not yet available.

Distribution

#### Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

### Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A

Ocean Shipment (IMDG)

Road Shipment Information (DOT) Air Shipment (IATA)

Not subject to IMDG code.

Not subject to DOT regulations.

Not subject to IATA regulations.

### Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard

Communication Standard 29 CFR 1910.1200.

**TSCA Status** All chemical substances found in this product comply with the

Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section

302 Extremely

Hazardous Substances

SARA Titre III Section None

304 CERCLA Substances

dangereuses

SARA Title III Section

311/312

SARA Title III Section 313 Toxic Chemicals

California Proposition

No components subject to 40 CFR 370

None present or none present in regulated quantities.

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth

defects or other reproductive harm: None known

#### Section 16. Other Information

**Revision Date** Disclaimer

1/15/2015

The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.